

SX-2016



■用途

OA・AV機器、Bluetooth・無線LAN等の近距離無線

■特長

- 超小型、超薄型、超軽量(2.0×1.6×0.4)のSMD水晶振動子
- Ceramic package
- 高信頼性、高精度



■仕様

| Type | SX-2016 | |
|---|----------------------|----------------------|
| Nominal frequency range | 24.000 ~ 54.000 MHz | |
| Crystal cut | Fundamental [AT-cut] | |
| Storage temperature range | -40~+90°C | |
| Operating temperature range | -10~+60°C | -30~+85°C |
| Frequency temperature characteristics (Ref. to +25°C) | ±10×10 ⁻⁶ | ±15×10 ⁻⁶ |
| Frequency tolerance(at +25°C) | ±10×10 ⁻⁶ | |
| Equivalent series resistance | 100 Ω : | 24.000 ~ 29.999 MHz |
| | 80 Ω : | 30.000 ~ 35.999 MHz |
| | 60 Ω : | 36.000 ~ 54.000 MHz |
| Load capacitance | 8pF, 12pF | |
| Shunt capacitance | 5pF max. | |
| Level of drive | 10μW(100μW max.) | |

梱包数量: 1,000pcs max./Reel

上記以外の仕様をご希望の際は、別途当社営業窓口までお問い合わせ下さい。

■外形・寸法 [単位:mm]

