

## SX-3225



### ■用途

OA・AV機器、Bluetooth・無線LAN等の近距離無線、携帯電話

### ■特長

- 超小型、超薄型(3.2×2.5×0.6)のSMD水晶振動子
- Ceramic package
- Seam Sealed
- 高信頼性



### ■仕様

Type	SX-3225	
Nominal frequency range	12.000 ~ 54.000 MHz	
Crystal cut	Fundamental [AT-cut]	
Storage temperature range	-40~+90°C	
Operating temperature range	-10~+60°C	-30~+85°C
Frequency temperature characteristics (Ref. to +25°C)	±10×10 <sup>-6</sup>	±15×10 <sup>-6</sup>
Frequency tolerance(at +25°C)	±10×10 <sup>-6</sup>	
Equivalent series resistance	100 Ω : 12.000 ~ 15.999 MHz 80 Ω : 16.000 ~ 18.999 MHz 60 Ω : 19.000 ~ 29.999 MHz 40 Ω : 30.000 ~ 54.000 MHz	
Load capacitance	series,10pF,12pF,16pF	
Shunt capacitance	5pF max.	
Level of drive	10μW(100μW max.)	

梱包数量:1,000pcs max./Reel

上記以外の仕様をご希望の際は、別途当社営業窓口までお問い合わせ下さい。

### ■外形・寸法 [単位:mm]

