

## SX-5032



### ■用途

携帯電話・PHS・Cordless Telephones・Pagers

### ■特長

- 小型、薄型 (5.0×3.2×0.7) のSMD水晶振動子
- Ceramic package
- Seam Sealed
- 高信頼性



### ■仕様

Type	SX-5032	
Nominal frequency range	8.000 ~ 54.000 MHz	
Crystal cut	Fundamental [AT-cut]	
Storage temperature range	-40~+90°C	
Operating temperature range	-10~+60°C	-30~+85°C
Frequency temperature characteristics (Ref. to +25°C)	±10×10 <sup>-6</sup>	±15×10 <sup>-6</sup>
Frequency tolerance(at +25°C)	±10×10 <sup>-6</sup>	
Equivalent series resistance	60 Ω : 8.000 ~ 10.999 MHz 50 Ω : 11.000 ~ 11.999 MHz 40 Ω : 12.000 ~ 24.999 MHz 30 Ω : 25.000 ~ 54.000 MHz	
Load capacitance	series,10pF,12pF,16pF	
Shunt capacitance	5pF max.	
Level of drive	10μW(100μW max.)	

梱包数量: 1,000pcs max./Reel

上記以外の仕様をご希望の際は、別途当社営業窓口までお問い合わせ下さい。

### ■外形・寸法 [単位:mm]

