

SX-6035



■用途

携帯電話・PHS・Cordless Telephones・Pagers

■特長

- 小型、薄型 (6.0×3.5×0.9) のSMD水晶振動子
- Ceramic package
- Seam Sealed
- 高信頼性



■仕様

Type	SX-6035	
Nominal frequency range	8.000 ~ 50.000 MHz	
Crystal cut	Fundamental [AT-cut]	
Storage temperature range	-40~+90°C	
Operating temperature range	-10~+60°C	-30~+85°C
Frequency temperature characteristics (Ref. to +25°C)	±10×10 ⁻⁶	±15×10 ⁻⁶
Frequency tolerance(at +25°C)	±10×10 ⁻⁶	
Equivalent series resistance	80 Ω : 8.000 ~ 8.999 MHz 60 Ω : 9.000 ~ 9.999 MHz 50 Ω : 10.000 ~ 11.999 MHz 40 Ω : 12.000 ~ 24.999 MHz 30 Ω : 25.000 ~ 50.000 MHz	
Load capacitance	series,10pF,12pF,16pF	
Shunt capacitance	5pF max.	
Level of drive	10μW(100μW max.)	

梱包数量: 1,000pcs max./Reel

上記以外の仕様をご希望の際は、別途当社営業窓口までお問い合わせ下さい。

■外形・寸法 [単位:mm]

TOP VIEW

#1, #3: Crystal terminal / #2, #4: Connected to cover.
(Please connect it with GND.)

Example of a Terminal Land Pattern

Maximum marking length		Marking
line1	line2	
7	7	Laser
ex.)		
<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;"> 16.0GA SIWARD </div>		